




Head and Base (1:2)




Front Elevation (TTS)



Rear Elevation (TTS)



Door Stiles (1:2)



Door Specification

Model:	F44-SG	Central Single Glazed Door	
Colour:	B	Black RAL9005 (30% gloss)	
Hand:	*	see qty/hand/size table	
Glass A:	T10	10mm toughened glass	29 (-1;-1) dB Rw Test 33: F44-SG-T10-01
Glass B:	T12	12mm toughened glass	34 (-1;-2) dB Rw Test 28: F44-SG-T12-01
Glass C:	T12	12mm toughened glass (no dropseal)	25 (-1; 0) dB Rw Test 29: F44-SG-T12-02
Glass D:	T13	13.5mm toughened laminate glass	37 (-1;-3) dB Rw Test 31: F44-SG-T13A-01
Hinge:	3S	3x H102R butt hinges	
Handle:	LV	19mm SSS levers	
Mortise:	GL	GB lever-only	
Lock:	NL	no lock	
Drop-seal:	D	acoustic drop-seal (Glass C / Test 29, no dropseal)	
Edge-seal:	BB	black brush edge seal	

Acoustic Test

Test Number:	024173 (see Spec for individual test numbers)
Test Centre:	SRL Technical Services, Sudbury, CO10 0TF
Test Date:	4th/5th/6th February 2019
Test Standard:	BS EN ISO 10140-2:2010, conforms to 140-3:1995
Rating Standard:	BS EN ISO 717-1:2013
Specimen:	UKAS accredited test lab 2.0 x 2.2m doorset rig



**F44-SG**

Door  
User  
Site

Series FY-AT-19-01  
SRL Technical Services

Title  
Drawn  
Sheet

F44-SG Performance Data Sheet  
NC  
1 of 1

Date  
Dwg  
Issue

08/02/2019  
FY-2354  
1

IP | Design Right | Copyright | Fyotto

